

Wall mounted unit

FTXB-C - INVERTER



INVERTER



Econo mode



Energy saving during standby mode



Comfort mode



Vertical auto swing

Wall mounted unit for low energy consumption and pleasant comfort

- Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- 24 hour timer can be set to start heating or cooling anytime during a 24 hour period

FTXB-C + RXB-C



Indoor unit		FTXB	25C	35C	50C	60C
Casing	Colour		White			
Dimensions	Unit	HeightxWidthxDepth	mm	283x770x216	310x1,065x224	
Sound power level	Cooling/Heating		dBA	55/55	58/58	55 61
Sound pressure level	Cooling	Super high/High/Nom./Low/Silent operation	dBA	-/40/33/26/21	-/41/34/27/23	44/40/38/35/32 46/43/41/37/33
	Heating	Super high/High/Nom./Low/Silent operation	dBA	-/40/34/28/25	-/41/35/29/26	44/40/38/35/32 46/43/41/37/33
Control systems	Infrared remote control		ARC470A1		-	

Efficiency data			FTXB + RXB	25C + 25C	35C + 35C	50C + 50C	60C + 60C	
Cooling capacity	Min./Nom./Max.		kW	1.3/2.5/3.0	1.3/3.3/3.8	1.630/5.480/6.200	1.750/6.230/6.500	
Heating capacity	Min./Nom./Max.		kW	1.3/2.8/4.0	1.3/3.5/4.8	1.170/5.620/6.600	1.200/6.400/7.100	
Power input	Cooling	Min./Nom./Max.	kW	0.310/0.770/1.050	0.290/1.030/1.300	0.280/1.700/1.910	0.280/1.931/2.000	
	Heating	Min./Nom./Max.	kW	0.250/0.700/1.110	0.290/0.940/1.290	0.240/1.500/1.880	0.240/1.680/2.000	
Seasonal efficiency (according to EN14825) 	Cooling	Energy label		A+				
		Pdesign	kW	2.50	3.30	5.48	6.23	
		SEER		6.02	6.05	5.93	6.09	
			Annual energy consumption	kWh	145	191	324	359
	Heating (Average climate)	Energy label		A+				
		Pdesign	kW	2.40	2.80	3.64	3.80	
		SCOP		4.01	4.06	4.27	4.06	
			Annual energy consumption	kWh	838	966	1,195	1,311
	Nominal efficiency	EER			3.25	3.21	3.22	3.23
COP				4.01	3.71	3.75	3.81	
Annual energy consumption		kWh		385	514	851	964	
Energy label		Cooling/Heating		A/A				

Outdoor unit				RXB	25C	35C	50C	60C
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275		753x855x328	
Sound power level	Cooling			dBA	60	62	64	65
	Heating			dBA	61	62	64	65
Sound pressure level	Cooling	High/Nom.		dBA	46/-	48/-	-/51	
	Heating	High/Nom.		dBA	47/-	48/-	-/51	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46			
	Heating	Ambient	Min.~Max.	°CWB	-15~18			
Refrigerant	Type/GWP				R-410A/2,087.5			
	Charge			kg/TCO ₂ eq	0.74/1.5	1.0/2.1	1.45/3.0	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240			

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load


Contains fluorinated greenhouse gases

Daikin Air Conditioning South Africa (Pty) Ltd
Head Office and Cape Town Sales
 Tel: (021) 528 3500 - Fax: (021) 551 8434
 E-mail: capesales@daikin.co.za - info@daikin.co.za

Daikin Air Conditioning South Africa (Pty) Ltd
Durban Sales
 Tel: (031) 263 2992 - Fax: (031) 263 2730
 E-mail: dbnsales@daikin.co.za

Daikin Air Conditioning South Africa (Pty) Ltd
Johannesburg Sales
 Tel: (011) 997 4400- Fax: (011) 997 4444
 E-mail: ihbsales@daikin.co.za

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-027

03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.